

PS Solar Pump Systems

Submersible Pump Systems, 4" and 6"

Applications

- drinking water supply
- livestock watering
- pond management
- irrigation
- etc.

Characteristics

- fast, failure-free installation
- excellent serviceability
- high reliability and life expectancy
- short Return of Investment (ROI) cycle
- lower Total Cost of Ownership (TCO)



PS1800 C-SJ5-12

PS1200 HR-03H

pictures may differ from actual products

Helical Rotor (HR) Types

pump system		PS200 HR	PS600 HR	PS1200 HR	PS1800 HR	PS4000 HR	
max. total dynamic head (TDH)	[m ft]	50 170	180 590	240 790	250 820	350 1,150	
max. flow rate	[m³/h 1,000 US gal./h]	2.7 0.7	2.7 0.7	2.7 0.7	4.0 1.1	2.4 0.6	
solar operation:	max. power voltage (Vmp)*	[VDC]	>34	>68	>102	>102	>238
	open circuit voltage (Voc)	[VDC]	max. 100	max. 150	max. 200	max. 200	max. 375
	nominal voltage	[VDC]	24–48	48–72	72–96	72–96	168–192
battery operation:	nominal voltage	[VDC]	24–48	48	72–96	72–96	n.a.

Centrifugal (C) Types

pump system		PS150 C	PS600 C	PS1200 C	PS1800 C	PS4000 C	
max. total dynamic head (TDH)	[m ft]	20 65	25 80	40 130	100 330	170 560	
max. flow rate	[m³/h 1,000 US gal./h]	5.0 1.3	11 2.9	20 5.3	51 13.5	70 18.5	
solar operation:	max. power voltage (Vmp)*	[VDC]	>17	>68	>102	>102	>238
	open circuit voltage (Voc)	[VDC]	max. 50	max. 150	max. 200	max. 200	max. 375
	nominal voltage	[VDC]	12–24	48–72	72–96	72–96	168–192
battery operation:	nominal voltage	[VDC]	12–24	48	72–96	72–96	n.a.

*) PV modules at standard test condition: AM = 1.5, E = 1,000W/m², cell temperature: 25 °C

Controller: PS

- controlling and monitoring
- control inputs for well probe, dry running protection, remote control etc.
- protected against reverse polarity, overload and high temperature
- solar operation: integrated MPPT (Maximum Power Point Tracking)
- battery operation: low voltage disconnect

Motor: ECDRIVE HR/C

- maintenance-free brushless DC motor
- water-filled
- no electronics in the motor
- submersion max. 250 m water column, IP68
- premium materials

Pump End: PE HR/C

- high life expectancy
- non-return valve
- premium materials
- optional: dry running protection

For further details visit www.lorentz.de

PS Solar Pump Systems

Surface Pump Systems

Applications

- drinking water supply
- livestock watering
- pond management
- water circulation through swimming-pool filter systems or thermal collectors
- pressurising home water systems
- irrigation
- etc.

Characteristics

- fast, failure-free installation
- excellent serviceability
- high reliability and life expectancy
- short Return of Investment (ROI) cycle
- lower Total Cost of Ownership (TCO)



PS150 Boost



PS600 CS-15-1*



PS1800 CS-36-1

pictures may differ from actual products

pump system		PS150 Boost	PS600 CS-15-1*	PS1800 CS-36-1	
max. total dynamic head (TDH)	[m ft]	120 400	14 45	16 55	
max. flow rate	[m³/h 1,000 US gal./h]	1.3 0.35	15 4.0	36 9.5	
solar operation:	max. power voltage (Vmp)**	[VDC]	> 17	> 68	> 102
	open circuit voltage (Voc)	[VDC]	max. 50	max. 150	max. 200
	nominal voltage	[VDC]	12–24	48–72	84–96
battery operation:	nominal voltage	[VDC]	12–24	48	96
pump type		positive displacement	centrifugal pump	centrifugal pump	
integrated strainer		-	■	■	
suitable for sea water		-	on request	on request	

**) PV modules at standard test condition: AM = 1.5, E = 1,000W/m², cell temperature: 25 °C

Controller: PS

- controlling and monitoring
- control inputs for well probe, dry running protection, remote control etc.
- protected against reverse polarity, overload and high temperature
- solar operation: integrated MPPT (Maximum Power Point Tracking)
- battery operation: low voltage disconnect

Motor: ECDRIVE Boost/CS

- maintenance-free brushless DC motor
- no electronics in the motor
- premium materials

Pump End: PE Boost/CS

- high life expectancy
- premium materials
- optional: dry running protection

*) PS600 CS-15-1 was formerly sold under the name PS600 BADU Top12. The product is identical.

For further details visit www.lorentz.de